



**abimac**

**ROTARY RAKE**

**BORELLO<sup>®</sup> 6800 SP**

*Performances for connoisseurs*



# ROTARY RAKE **BORELLO®** 6800 SP

## (CARRIED ON THREE POINTS WITH REAR SUPPORTING WHEELS)

TECHNICAL FEATURES	6800 SP
• Swath formation	central
• Hydraulic rotor width adjustment (0 to 40 cm)	standard
• Number of gearboxes in oil bath	2
• Working width with swath	6.40 - 6.80 m
• Number of fork arms	11 × 2
• Number of forks (spring teeth) per arm	4
• Extractable arms	standard
• Self-supporting frame with rear wheels and 2-point linkage to tractor	•
• Single-rotor working device	standard
• Rear steering axle	standard
• Number of pivoting wheels each rotor	4
• Tires	10 × 0.80 - 12
• Tyres for rotor	16 × 6.50 - 8
• Tandem axles	standard
• Width in transport position	2.50 m
• Total length (transport position)	5.50 m
• Weight with transmission	1750 kg
• Secondary transmission with PTO shaft and clutch	2
• Transmission with PTO shaft and fifth wheel	1
• Min. power required	55/40 Hp/Kw
• Lighting system for road transportation	standard



Manufactured by Abimac s.r.l.  
 Reg. Solere, 13 - 12038 Savigliano (CN) - Italy  
 tel. ++39 0172 377314 - fax ++39 0172 377288  
 info@abimac.it - www.abimac.it

Distributor: