


## **ROTARY RAKE**

## BORELLO® 3.5 F - S

The rotary rakes of the BORELLO series 3.5 are reserved to farmers who wish to make perfect fluffy swaths of dry and wet forage. A maintenance-free oil-bath gearbox garantees an excellent long life.



The BORELLO version 3.5 F with fixed frame is a very stable rake, easy to use even on steep hilly or mountain slopes.



The BORELLO version 3.5 S with steering frame and tandem axle with oxillating bearings and tandem axle supplies the highest stability particularly on ondulated or rough ground.

| TECHNICAL FEATURES      |  |   |  |  |
|-------------------------|--|---|--|--|
|                         | BORELLO 3.5 F  | BORELLO 3.5 S                               |  |  |
| • Gearbox 9 arms:       | in oil bath (maintenance free)   | in oil bath (maintenance free)              |  |  |
| Swath position:         | on the left hand side  | on the left hand side                       |  |  |
| • Linkage:              | carried on the three point linkage of the tractor with connection and steering wheels carried on the three point linkage of the tractor with steering connection |   |  |  |
| Working width:          | 3.50 m (including swath)   | 3.50 m (including swath)                    |  |  |
| • Transportation width: | 1.50 m   | 1.50 m                                      |  |  |
| • Arms:                 | 9  | 9   |  |  |
| • Tines per arm:        | 4  | 4   |  |  |
| • Axle:                 | with 4 wheels $15 \times 6.00 - 6$ (n° 2 in version fixed frame)   | with 4 wheels $15 \times 6.00$ 6            |  |  |
| • Transmission:         | 1 P.T.O. shaft<br>(free wheel upon request)  | 1 P.T.O. shaft<br>(free wheel upon request) |  |  |
| • Total weight:         | Kg. 420  | Kg. 460                                     |  |  |
| • P.T.O.:               | 540 r.p.m.   | 540 r.p.m.                                  |  |  |
| Required power:         | HP 50 / KW 37  | HP 50 / KW 37                               |  |  |



Manufactured by Abimac s.r.l. Reg. Solere, 13 - 12038 Savigliano (CN) - Italy tel. ++39 0172 377314 - fax ++39 0172 377288 info@abimac.it - www.abimac.it

| <b>-</b> |      |      |            |
|----------|------|------|------------|
| Dis      | trır | M IT | $\alpha r$ |
| $\nu$ 13 | UIL  | ut   | oı.        |