



ROTARY RAKE



BORELLO® 8200-13 SP

Performances for connoisseurs

ROTARY RAKE **BORELLO®** 8200-13 SP

(CARRIED ON THREE POINTS WITH REAR SUPPORTING WHEELS)

unfolded position (open)



folded position (closed)



Road width 2.50 m

TECHNICAL FEATURES	8200-13 SP
Swath formation	central
Hydraulic rotor width adjustment (0 to 80 cm)	standard
Number of gearboxes in oil bath	2
Working width with swath	7.80 - 8.20 m
Number of fork arms	13 × 2
Number of forks (spring teeth) per arm	4
Extractable arms	standard
Self-supporting frame with rear wheels and 2-point linkage to tractor	
Single-rotor working device	standard
Rear steering axle	standard
Number of pivoting wheels each rotor	4
Tires	10 × 0.80 - 12
Tyres for rotor	16 × 6.50 - 8
Tandem axles	standard
Width in transport position	2.50 m
Total length (transport position)	5.00 m
Weight with transmission	1950 kg
Secondary transmission with PTO shaft and clutch	2
Transmission with PTO shaft and fifth wheel	1
Min. power required	80/58 Hp/Kw
Lighting system for road transportation	standard



Manufactured by Abimac s.r.l.
 Reg. Solere, 13 - 12038 Savigliano (CN) - Italy
 tel. ++39 0172 377314 - fax ++39 0172 377288
 info@abimac.it - www.abimac.it

Distributor: